

## 1-BUTENE 1-C<sub>4</sub>H<sub>8</sub>

Colorless, flammable, liquefied gas with a mildly aromatic odor.

## **SHIPPING INFORMATION**

D.O.T. Proper Shipping Name: Butylene I.D. Number: UN1012 Hazard Class: 2.1

Shipping Labels: Flammable gas

## **TECHNICAL INFORMATION**

Molecular Weight: 56.108
Specific Volume: 6.7 ft³/lb.
CAS Registry 106-98-9
Safety Data Sheet Reference: 1-Butene

Grade Name	Grade	Minimum Purity	Grade Code	Catalog Number <sup>1</sup>	Maximum Impurity Specifications in PPM by Volume (unless otherwise specified) <sup>2</sup>		
					H2O	Sulfur	Sum of all Impurities <sup>3</sup>
Research	4.0	99.99%	RES	1BU RES-	2	1	100
Instrument	2.5	99.5%	INS	1BU INS-	10	0.5	< 0.5%
Chemical Pure	2.0	99%	CP	1BU CP-	10	0.5	< 1%

**Notes:** <sup>1</sup> Complete catalog number by selecting cylinder size code using chart below.

<sup>&</sup>lt;sup>3</sup> A complete list of impurities is available upon request.

CYLINDER INFORMATION											
Cylinder Size	Cylinder Size Code	Volume lbs. <sup>4</sup>	Pressure (PSIG) @ 70° F.	Valve Connection CGA <sup>5</sup>	Gross Weight (lbs.)						
Low Pressure Steel Cylinders											
Jumbo	HTN	540	23.5	510 / 555 SIPHON	874						
350	LP25	128	23.5	510 / 555 SIPHON	207						
LP5	LP5	25	23.5	510 / 555 SIPHON	42						

## Notes:

Contact your WestAir representative about equipment recommendations for this product.

1-866-937-8247

<sup>&</sup>lt;sup>2</sup> Liquid Phase Analysis. Specifications are typical results and are subject to change without notice.

<sup>&</sup>lt;sup>4</sup> This product is sold by the cylinder. Fill volumes are approximate and may vary slightly depending on the cylinder manufacturer's specifications.

 $<sup>^{5}</sup>$  Siphon tube with a CGA 555 for liquid withdrawal is available upon request. Add "S" at end of cylinder size code.