

## **1,3 BUTADIENE**



Colorless, flammable, liquefied with a mildly aromatic odor.

**SHIPPING INFORMATION** 

D.O.T. Proper Shipping Name: Butadienes
I.D. Number: UN1010
Hazard Class: 2.1

Shipping Labels: Flammable gas

**TECHNICAL INFORMATION** 

Molecular Weight: 54.092
Specific Volume: 6.9 ft³/lb.
CAS Registry 106-99-0
Safety Data Sheet Reference: 1,3 Butadiene

PRODUCT GRADE SPECIFICATIONS									
Grade Name Grade Minimum Purity		Grade Code	Catalog Number <sup>1</sup>	Maximum Impurity Specifications in PPM by Volume <sup>2</sup> (unless otherwise specified)					
					Sum of all Impurities <sup>3</sup>				
Chemical Pure	2.0	99%	СР	SG 13BCP-	< 1 %				

## Notes

<sup>&</sup>lt;sup>3</sup> A complete list of impurities is available upon request.

CYLINDER INFORMATION									
Cylinder Size	Cylinder Size	Volume⁴ 	Pressure (PSIG)	Valve Connection <sup>5</sup>	Gross Weight (lbs.)				
	Code	lbs.	@ 70° F.	CGA					
Low Pressure Steel Cylinders									
350	LP25	129	21.4	510 / 555	204				
LP5	LP5	25	21.4	510 / 555	43				
Disposable Non-Refillable Cylinders									
Lecture Bottle	LB*	0.375	21.4	*170	4.4				

## Notes:

Contact your WestAir representative about equipment recommendations for this product.

<sup>1</sup> Complete catalog number by selecting cylinder size code using chart below. Except for Disposables, "SG" will be replaced with "DSP".

<sup>&</sup>lt;sup>2</sup> Liquid Phase Analysis. Specifications are typical results and are subject to change without notice.

<sup>&</sup>lt;sup>4</sup> This product is sold by the cylinder. Fill volumes are approximate and may vary slightly depending on the cylinder manufacturer's specifications.

<sup>&</sup>lt;sup>5</sup> Siphon tube with a CGA 555 for liquid withdrawal is available upon request. Add "S" at end of cylinder size code.