

# **NITROUS OXIDE**

 $N_2O$ 

Colorless, odorless, nontoxic, liquefied nonflammable gas with a slightly sweet taste and odor.

### **SHIPPING INFORMATION**

D.O.T. Proper Shipping Name: Nitrous Oxide
I.D. Number: UN1070
Hazard Class: 2.2 (5.1)

Shipping Labels: Nonflammable Gas, Oxidizer

## **TECHNICAL INFORMATION**

Molecular Weight: 44.013
Specific Volume: 8.79 ft³/lb.
CAS Registry 10024-97-2
Safety Data Sheet Reference: Nitrous Oxide

PRODUCT GRADE SPECIFICATIONS													
Grade Name	Grade	Minimum Purity	Grade Code	Catalog Number <sup>1</sup>	Maximum Impurity Specifications in PPM by volume (unless otherwise specified) <sup>2</sup>								
					H₂O	THC (as CH <sub>4</sub> )	CO+ CO <sub>2</sub>	CO2	СО	N <sub>2</sub>	NO₂	NOx	NH₃
Electronic	5.5	99.9995%	EL	SG NXEL-	1	0.1		0.2	0.3	0.3	0.3	0.1	0.1
Ultra Plus	5.0	99.999%	UP	SG NXUP-	2	0.2		0.5	2	2	0.2	0.3	0.5
Lab & Spec	4.5	99.995%	LSG	SG NXLSG-	5	5	5			20	1	1	
Ultra High Purity	4.0	99.99%	UHP	SG NXUHP-	5	1		100	5		1	1	5
Atomic Absorption	2.6	99.6%	AA	SG NXAA-	5	20		300					25

#### Notes:

<sup>&</sup>lt;sup>2</sup> Liquid Phase Analysis. Specifications are typical results and are subject to change without notice. Product sold on the basis of total impurities. Individual impurities may vary slightly.

CYLINDER INFORMATION										
Cylinder Size <sup>3</sup>	Cylinder Size Code	Volume⁴ Lbs.	Pressure (PSIG) @ 70° F.	Valve Connection CGA	Gross Weight (lbs.)					
Carbon Steel Cylinders										
200	K	56	745	326	207					
80	Q	20	745	326	85					
Aluminum Cylinders										
150A	DA	40	745	326	44					
30A	GA	6	745	326	10					

#### Notes:

Also available in medical and food grades. Contact your WestAir representative for details.

Contact your WestAir representative about equipment recommendations for this product.

<sup>&</sup>lt;sup>1</sup> Complete the catalog number by selecting cylinder size code using chart below.

<sup>&</sup>lt;sup>3</sup> Syphon Tubes are available upon request for liquid withdrawal for select sizes and grades. Add "S" after cylinder size code

<sup>&</sup>lt;sup>4</sup> This product is sold by the cylinder. Fill volumes are approximate and may vary slightly depending on cylinder manufacturer.